



**NOTES:**

1. All Cast Iron Construction
2. Design B
3. IP55 Labyrinth seals on DE and ODE
4. H Class Insulation System
5. Max Winding Temperature rise 80°C
6. Max bearing temperature rise 45°C for 4 pole and 50°C for 2 pole motors when direct coupled.
7. Regreasable bearings
8. External Grounding provisions
9. Maximum foot flatness deviation .127 mm
10. Conductive Polymer Cooling Fan
11. Diagonally Split Conduit Box rotatable in 90° Increments
12. Lead seals in conduit box
13. Maximum no load sound power 85 dBA(2 pole),  
Maximum no load sound power 70 dBA(4 pole),  
Maximum no load sound power 64 dBA(6 pole).
14. No Load Motor Vibration not to exceed  
a.Radial 60HZ - 2.03mm/s (2,4 pole) and 1.52mm/s (6 pole)  
b.Axial 60HZ - 1.52mm/s
15. 300 series Stainless Steel hardware
16. Epoxy Coating meeting ASTM B117-97 for 96 h
17. All internal surfaces coated with anti-corrosion coating.
18. Internal Shaft Grounding brush installed on drive end.
19. No Load test report included with motor

**TECHTOP IEEE 841 SEVERE DUTY ELECTRIC MOTOR**

MODEL	SD3-445T-4-BR-E-150		TECHTOP.COM
NEMA Premium	60 Hz	50 Hz	T 445T150U4B
HP	150	150	SER # 1603102051
RPM	1785	1480	DATE 0688002
VOLT(3Ø)	460	380	DESIGN B
FLA	165	198	FRAME 445T
SF	1.15	1	ENCL TEFC
KVA CODE	G	E	IP 55
NOM.EFF	0.958		DUTY Cont.
			INS CL H
			AMB 40 °C
			WEIGHT 1685.2 lbs
			MADE IN CHINA

BEARING SIZE: DE 6319-23, ODE 6319-23  
VFD 15.1 CT-1.0 SF



<p><b>ShangHai HIMAK Electrical Machinery CO., LTD</b></p>		NEMA TEFC 445T-150HP-4P	
		IEEE-841 UNITS:INCH	
Design	Standard	NO:	CY260.A20.006
Checker	Allow	STEP MARK	1:6.5 SORT Cast iron Motor
Auditing	Date		