




FOOD GRADE HIGH TEMP LUBRICANT





LU™ 213


- 


NSF® Nonfood Compounds Program Listed H1 Rated (Registration # 145281)
- 


For use in high pressure applications
- 

Minimum - Maximum operational temperature range: Low 12 °F (-11 °C) • High 635 °F (335 °C)
- 

Meets (OECD) 301B Standards - Rapidly Biodegradable after 301B Standard
- 

Free of heavy metals such as Barium & Cadmium
- 

Contains P.T.F.E. (polytetrafluoroethylene)
- 

HMIS Hazard Rating: Health (2) • Flammability (3) • Reactivity (0)
- 

- High Temperature Performance
- Fortified With Extreme Pressure and Anti-Wear Additives
- Foaming Action For Excellent Cling and Penetration



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™213 Food Grade High Temp Lubricant is a blend of the finest quality renewable resource oils available, treated with the most effective anti-oxidants, extreme pressure, anti-wear, and corrosion protecting additives. PTFE is added to further enhance load capacity, and reduce friction. LU™213 Food Grade High Temp Lubricant offers excellent extreme pressure lubricity, water resistance and high temperature (12 °F to 635 °F) performance on chains and much more. Foaming action allows for pin-point application and penetration.

LUBRICANTS

FOR USE ON

- Ovens • Dryers
- Gears • Conveyors
- Wire Ropes • Hoists
- Rollers • Cams
- Slide Bearings
- Anything Requiring Extreme Temperature Performance

FOR USE BY

- Bakeries • Bottlers
- Breweries • Canneries
- Dairies • Egg Processors
- Meat & Poultry Processors



LU213

APPLICATION

Shake well before using. For best results use at room temperature 70° F. Spray in a well ventilated area away from open flame. Apply a thin film and allow to soak in. Only use necessary amount to achieve desired results. Wipe off excess with clean cloth. Use extension tube for hard to reach areas

PERFORMANCE

PLASTIC & RUBBER SAFE: Yes
(Always test before using)
TEMPERATURE RANGE:
HIGH: 635°F
LOW: 12°F
LOAD CAPACITY: Extreme
DIELECTRIC STRENGTH: 46.5 kV
FALEX LOAD (ASTM D-3233A): 3,750 lbs.
4-BALL WEAR SCAR (ASTM D-2266): 0.44mm
RAPIDLY BIODEGRADABLE (OECD-301): Yes
DELIVERY: SPRAY ANYWAY™

PACKAGING

STOCK #: S00213000
UPC CODE: 0-75577-00623-6
FILL WT.: 15 oz.
PER CASE: 12
CARTON DIMENSIONS:
L 11.13" x W 8.44" x H 9.94"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS: Sprayon.com
CUSTOMER SERVICE: 800-777-2966
TECHNICAL INFORMATION: 800-251-2486

PROPERTIES

APPEARANCE: Light Straw Color
BASE: Bio-based (Vegetable)
FILM TYPE: Wet
CONTAINS P.T.F.E.: Yes
ODOR: Low
PROPELLANT: Hydrocarbon Blend
WT./GAL.: 6.86
SPECIFIC GRAVITY: 0.83
% VOC AEROSOL: 15
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
HEAVY METALS: No
FLAMMABLE: Yes
FLASH POINT: <0 °F
SARA 313: None
PROP 65: None
HAPS: None
HAZARD RATING: 2, 4, 0
SHELF LIFE: 3 years from date of manufacture

NSF® NONFOOD COMPOUNDS PROGRAM LISTED

H1 Rated - Registration #145281



This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.



Scan this code with your mobile phone to download the NSF® Registration Letter for this product

© 2012 Sprayon® Products Made in U.S.A.

Distributed by:

USA Roller Chain & Sprockets
sales@usarollerchain.com
(407) 347-3519

PRESERVE. PROTECT. PREVENT.®



Sprayon® Products
101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
800-777-2966

310-PDS-LU213